

1 **IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

2
3 **TITLE OF THE INVENTION**

4 Optically Generated Isolated Feedback Stabilized Bias.

5 **CROSS-REFERENCE TO RELATED APPLICATIONS**

6 Not Applicable.

7 **STATEMENT REGARDING FEDERALLY SPONSORED**

8 **RESEARCH OR DEVELOPMENT**

9 Not Applicable.

10 **BACKGROUND OF THE INVENTION**

11 Field of the Invention. The invention is generally related to electrical bias voltage
12 generation and more specifically to the optical generation of an adjustable, stable, low-
13 noise, electronically isolated bias for use with precision analytical equipment.


14 Description of the Related Art. The generation of bias voltages is widely known
15 in the field of analytical chemistry. Equipment used to detect very small levels of charge
16 use a bias voltage to produce an accelerating field in ion detectors, such as
17 chromatographic ionization detectors.

CERTIFICATE OF MAILING UNDER 37 C.F.R. §1.10

I hereby certify that this correspondence is being deposited with the United States Postal Service on the date shown below in an envelope as "Express Mail Post Office to Addressee": Mailing Label Number ER216163965US to MAIL STOP: Patent Application, Commissioner for Patents, Post Office Box 1450, Alexandria, Virginia 22313-1450.

Date: _____

7/15/03



Kenneth A. Keeling
Registration No. 31,842

1 A chromatographic ionization detector operates by applying a high voltage across
2 discharge electrodes that are located in a gas-filled source chamber. In the presence of a
3 detector gas such as helium, a characteristic discharge emission of photons occurs. The
4 photons irradiate an ionization chamber receiving a sample gas that contains an analyte of
5 interest. Ions are produced in the ionization chamber as a result of photon interaction with
6 ionizable molecules in the sample gas. Such detectors are well known in the art and
7 include U.S. Patent 5,767,683 issued June 16, 1998 to Stearns, Cai and Wentworth, U.S.
8 Patent 5,594,346 issued January 14, 1997 to Stearns and Wentworth, and U.S. Patent No.
9 5,541,519 issued July 30, 1996 to Stearns and Wentworth.

10 The sensitivity and resolution of detection equipment may be limited by the
11 stability of the bias voltage and the extraneous electrical variations, or noise, created by
12 associated electrical circuits. Voltage variations in the bias and/or leakage currents
13 produced by the bias may mask the desired occurrences to be measured.

14 Simple bias voltage may be generated from a 12V DC power supply. Transistors
15 and integrated circuit converters are used to modify the frequency and voltage of the
16 current from the power supply to obtain a desired bias. Further transistorized circuitry
17 may be used to filter and monitor the current and voltage in order to achieve a useable
18 degree of stability.

19 Bias generation in the prior art has typically involved the use of transformer-
20 coupled circuits in which a first transformer, driven by an alternating-current source, is
21 connected to a second transformer whose isolated output is then rectified, filtered, and
22 regulated at a predetermined voltage by additional circuitry. Disadvantages of this

1 scheme include: the output bias voltage is not adjustable without additional feedback
2 circuitry; variations in the output bias voltage are not sensed and regulated without
3 additional feedback circuitry; AC electromagnetic fields may be coupled to the detecting
4 circuitry, causing instability in the measurement process without additional shielding; and
5 the number of components required may increase the cost and reduce the reliability of the
6 employing device.

7 Diodes are known to be able to produce light when a current is passed through, or
8 to generate a current when excited by a light source. In both cases, the intensity of the
9 light is proportional to the magnitude of the current.

10 Incident with a current flow through a diode is a voltage drop across the diode.
11 The relationship between the current and the voltage is given by the well-known diode
12 equation:

13
$$I_D = I_S e^{K(T - T_0)} [e^{V/V_t} - 1]$$

14 where

15 I_S is the saturation current, fixed by the materials and fabrication of the diode
16 (amps);

17 K is a constant for the material used for the diode, approximately 0.045 for
18 silicon;

19 T is the diode temperature (°K);

20 T_0 is the diode reference temperature (°K);

21 V_t is the threshold voltage, 0.026 volts (V);

22 V is the voltage through the diode (V);

1 e is the electron charge (1.602×10^{-19} C);
2 K is Boltzmann's Constant (1.380×10^{-23} J/K); and
3 λ is a constant for the material used for the diode, approximately 2 for
4 silicon.

5 Of importance is that diode current and voltage drop are not linearly proportional and are
6 influenced by temperature. For illustration of the influence of temperature, where $I_S =$
7 $1.0\text{E-}9$ amperes, $T - T_0 = 0$ and $V = 0.036$ volts, then $I_D = 1.0\text{E-}9$ amperes; in the same
8 example where $V = 0.36$ volts, then $I_D = 1.0\text{E-}6$ amperes. If at $V = 0.36$ Volts, diode
9 temperature, T , rises such that $T - T_0 = 10^\circ\text{C}$, then $I_D = 1.57\text{E-}6$ amperes.

10 In a practical photovoltaic diode circuit, some type of device or load will be
11 externally connected to the photovoltaic diode. When the effect of such a load is added
12 to the diode equation the equation becomes:

13
$$I_D = I_S e^{K(T - T_0)} [e^{V/\lambda V_t} - 1] + V/R_L$$

14 where I_D is the total generated current and R_L is the value of the load, in ohms.

15 Anomalies in a power supply and environmental conditions, such as temperature
16 and humidity affect the electrical current produced by an electrical circuit. The voltage
17 supplied to the load is subject to such anomalies. A practical photovoltaic diode circuit
18 requires some means of control and stabilization of the generated voltage. Some
19 examples of prior art circuits designed to compensate for voltage variations in circuits
20 include:

21 U.S. Patent No. 4,375,596, issued on March 1, 1983, to Hoshi, discloses a
22 reference voltage generator circuit, which overcomes variations in a power supply by

1 dividing the power supply voltage to create two output signals, uniformly modifying the
2 signals in opposite polarity, then averaging the resulting signals to generate a constant
3 value of reference voltage.

4 U.S. Patent No. 4,380,706, issued on April 19, 1983, to Wrathall, discloses a
5 temperature stable voltage reference source, which uses a differential amplifier with an
6 output coupled to an additional amplifying stage, involving two bipolar transistors,
7 wherein the emitter of one transistor is larger than the emitter of the other transistor.
8 Cascaded emitter followers are used between the two amplifying stages to develop a
9 higher voltage, which is fed back into the inputs of the differential amplifier, thereby
10 establishing a more independently stable reference voltage circuit.

11 U.S. Patent No. 4,471,290, issued on September 11, 1984, to Yamaguchi,
12 discloses a substrate bias generating circuit responsive to the output signal of the
13 oscillator circuit, which includes a voltage divider connected between the output terminal
14 of the bias generating circuit and a ground terminal, and a level sensor for producing a
15 control signal to the oscillator circuit when it is detected that the output voltage of the
16 voltage divider reaches a predetermined value, to thereby stop the oscillating operation of
17 the oscillator circuit

18 U.S. Patent No. 5,262,989, issued on November 16, 1993, to Lee et al., discloses a
19 circuit for sensing back-bias levels in a semiconductor device that causes the voltage
20 pump circuit to adjust output to reach and maintain a desired voltage level.

21 U.S. Patent No. 3,975,649, issued on August 17, 1976, to Kawagoe et al.,
22 discloses a temperature compensation circuit that uses a high value resistor and at least

1 one field-effect transistor for connection between a circuit to be compensated and the
2 power source, such that the when ambient temperature of the circuit increases the current
3 flowing through the field-effect transistor decreases. However, the decreased current
4 from the field-effect transistor causes voltage drop across the resistor to decrease. With
5 the opposite end of the resistor connected to the gate of the field-effect transistor, the
6 relative increase in voltage causes an increased current flow through the field-effect
7 transistor, compensating for the temperature fluctuation to stabilize the output voltage.

8 U.S. Patent No. 4,794,247, issued on December 27, 1988, to Stineman, Jr.,
9 discloses using an integrating amplifier with a feedback capacitor, to stabilize the bias
10 signal from a photovoltaic detector, while reducing the noise effect.

11 U.S. Patent No. 4,843,265, issued on June 27, 1989, to Jiang, discloses a
12 temperature compensating circuit that generates inverse variations in a field-effect
13 transistor, achieved by charging a capacitor to a voltage and discharging the capacitor
14 through a field-effect transistor in response to the fluctuations.

15 Also known to the field of art is the use of photovoltaic diodes to produce a
16 current isolated from the current of the light source. Light sources capable of exciting
17 current in photovoltaic diodes include light-emitting diodes. Prior art that demonstrates
18 these uses include:

19 U.S. Patent No. 5,805,062, issued on September 8, 1998, to Pearlman, discloses
20 an isolation amplifier that transmits data to a receiver via a current loop, where the
21 isolated portion of the circuit is powered by a photovoltaic array illuminated by a light
22 source, optionally an array of same frequencied light-emitting diodes.

A device is commercially available, referred to as an optically coupled floating power source, that is composed of one or more light-emitting diodes and one or more photovoltaic diodes, disposed within an opaque package in such a way that light from the light-emitting diodes impinge on the photovoltaic diodes, thereby generating a current in the photovoltaic diodes in response to the current supplied to the light-emitting diodes.

It would be an improvement to the field to create a bias voltage from a power source comprised of at least one light-emitting diode stimulating matched currents in at least two electrically isolated photovoltaic diodes, such that the circuit of one diode is used to provide a feedback voltage to an operational amplifier driving the light-emitting diode, thereby stabilizing the output voltage in both of the photovoltaic diode circuits.

It would be a further improvement to provide a distance between the bias source and detector due to the temperature of the detector. Such distance however typically requires shielding of the connection between the electronics and the detector, typically by coaxial cabling. The use of such shielding introduces capacitance which creates a pathway into the electronics for current noise resulting from the voltage noise in the bias generator. Low noise in the bias generator therefore becomes more critical under these circumstances.

BRIEF SUMMARY OF THE INVENTION

Accordingly, the objects of this invention is to provide, *inter alia*, an electrical circuit for generating a bias voltage that:

- 1 • provides sufficient voltage stability for highly precise analytical measuring
2 equipment, including chromatographic ionization detectors has low noise
3 production;
- 4 • has the output circuit electrically separated from the drive and feedback circuit;
- 5 • provides a stabilizing feedback voltage to a drive amplifier; and
- 6 • provides the ability to set and vary the generated voltage of the circuit.

7 Other objects of my invention will become evident throughout the reading of this
8 application.

9 The current invention is an electrical circuit for detection equipment, such as
10 chromatographic ionization detectors, for the generation of a stable, low-noise bias,
11 having at least one set of one or more light-emitting diodes (LED) and at least two
12 photovoltaic diode sets disposed in such a way that light from each light-emitting diode
13 impinges on at least two photovoltaic diode sets, thereby generating a current in the
14 photovoltaic diode sets in response to current supplied to the light-emitting diode. The
15 photovoltaic diode set may include two or more photovoltaic diodes. The current from
16 one photovoltaic diode set produces the output voltage, while the current of the other
17 photovoltaic diode set feeds into an amplifier, which regulates the drive current to the
18 light-emitting diode set. Fluctuations in the current produced in the photovoltaic diode
19 set in the output circuit are identically, though independently, represented in the other
20 photovoltaic diode, which in turn causes a corresponding adjustment in the drive current
21 to the light-emitting diode to correct the fluctuation. The result is an essentially stable

1 output voltage. (The term "essentially", as used herein, means closely approximating to a
2 degree sufficient for practical purposes.)

3 BRIEF DESCRIPTION OF THE DRAWINGS

4 Figure 1 is a simplified schematic of a bias generation circuit in accordance with
5 the present invention.

6 Figure 2 is a simplified schematic of a bias generation circuit in accordance with
7 the present invention, having multiple light-emitting diodes in series.

8 Figure 3 is a dissected simplified schematic of the electrically isolated controlled
9 circuit of the bias generation circuit of Fig. 2.

10 Figure 4 is a dissected simplified schematic of the electrically isolated controlling
11 circuit of the bias generation circuit of Fig. 2.

12 Figure 5 is a simplified schematic of a bias generation circuit in accordance with
13 the present invention having a potentiometer for equalization of current output from the
14 two photovoltaic diode sets to correct for any differences in output of the two
15 photovoltaic diode sets.

16 DESCRIPTION OF THE INVENTION

17 Referring to Fig. 1, the present invention provides a bias generation circuit 10 in
18 which an optically coupled power source 11 generates identical currents within
19 electrically isolated circuits. Optically coupled power source 11 comprises light emitting
20 diode 35, connected to ground 29 at its anode end and to resistor 15, then on to output 80
21 of operational amplifier 13 on its cathode end. Light emitting diode 35 is disposed in
22 such a way that the light from light emitting diode 35 impinges equally on controlled

1 photovoltaic diode set 36 and controlling photovoltaic diode set 37. Controlled
2 photovoltaic diode set 36 and controlling photovoltaic diode set 37 thereby respectively
3 generate essentially equivalent, electrically isolated controlled current 60 and controlling
4 current 70. In the preferred embodiment, optically coupled power source 11 is a
5 commercially available circuit chip, DIG-12-8-30, by Dionics, Inc.

6 Controlled photovoltaic diode set 36 is connected into controlled circuit 30.
7 Output node 25 connects to the anode end of controlled photovoltaic diode set 36 and
8 input node 26 connects to the cathode end of controlled photovoltaic diode set 36. Also
9 connected between input node 26 and output node 25, parallel with controlled
10 photovoltaic diode set 36 are resistors 24 and 12. In the exemplary embodiment, resistor
11 pairs 24 and 12, and 22 and 23, possess equivalent resistance.

12 Controlling photovoltaic diode set 37 is connected into controlling circuit 32.
13 Positive output node 18 connects to the anode end of controlling photovoltaic diode set
14 37. Positive output node 18 is also connected to a reference voltage source 16, which is
15 adjustable. In the exemplary embodiment, reference voltage source 16 is set to +10 volts.
16 Node 17 connects to the cathode end of controlling photovoltaic diode set 37. Node 17
17 also connects to resistor 23, which in turn connects to node 20. Resistor 22 connects to
18 node 20 on one end and to node 18 on the other. Resistors 23 and resistor 22 possess
19 equivalent resistance.

20 Non-inverting input 84 of operational amplifier 13 is connected to ground 19.
21 Inverting input 82 of operational amplifier 13 is connected to node 20 and to one side of

1 capacitor 14. Output 80 of operational amplifier 13 is connected to resistor 15 and the
2 other side of capacitor 14.

3 Referring to Fig. 1, operational amplifier 13, well known to those skilled in the
4 art, produces an output voltage proportional to the difference between the voltages at the
5 input nodes as:

6
$$V_0 = A (V^+ - V^-)$$

7 where V_0 is the output voltage, V^+ is the non-inverting input node voltage, V^- is the
8 inverting input node voltage, and A is the gain factor, usually on the order of 10^6 . Under
9 conditions of stable operation, the magnitude of V_0 will be less than a few volts (*e.g.*, <
10 10 volts), and the input voltage difference, $V^+ - V^-$, will therefore be less than V_0 / A
11 (*e.g.*, < 10 micro-volts). For practical purposes, the input voltage difference may then be
12 considered to be zero.

13 Introducing drive current 50, through light emitting diodes 35, activates circuit 10.
14 The light emitted by light emitting diodes 35, induces driven output current 60 and driven
15 feedback current 70.

16 Under stable operating conditions, equal currents 60 and 70 are produced by
17 photovoltaic diode sets 36 and 37, respectively, the voltage across resistors 12 and 24, is
18 equal to the voltage across resistors 22 and 23, the voltage at node 17, is equal in
19 magnitude and opposite in sign to the voltage at node 18, and the voltage at node 20,
20 (since the resistors 22 and 23, are of equal value) is essentially zero. The electrically
21 isolated voltage source at nodes 25 and 26 is used as the desired stable generated bias.

1 The equality of current 60 and 70 contains natural variations, possibly due to non-
2 uniform transmission of light energy simultaneously to diode 36 and 37 from diode 35,
3 the physical characteristics of diodes 36 and 37 not being completely identical, or other
4 variation sources. In the exemplary embodiment shown in Figure 5 these variations are
5 adjusted by inserting the adjustable contact of potentiometer 201 to node 20, between
6 resistors 22 and 23, which alters the ratios of values of resistors 22 and 23 while keeping
7 the sum of their values constant. The total resistance through the potentiometer 201 at
8 node 20, and resistors 22 and 23 would equal the total resistance through resistors 12 and
9 24. Alternatively, the ratio of resistors 22 and 23 could be left constant and the
10 configuration of resistors 12 and 24 could be altered to adjust the sum of resistors 12 and
11 24, in order to correct the imbalances as they occurred. As a further alternative,
12 potentiometer 201 could be replaced with a resistor of resistance equal to potentiometer
13 201 (not shown) Other equivalent solutions are known to the field, which may be
14 employed to manipulate the ratio and sum of the resistance values between nodes 17 and
15 18 with the resistance values between nodes 25 and 26.

16 Referring to Fig. 1, bias generation circuit 10 is configured to seek a stable
17 condition. Since both photovoltaic diode pairs 36 and 37 are subject to the same
18 conditions of loading – illumination, temperature, etc. – the voltage difference between
19 nodes 25 and 26 will be the same as the voltage difference between nodes 18 and 17.
20 Although the voltage at node 18 is set by reference source 16 to be +10 volts in the
21 following examples, the condition for stability is not dependent on the magnitude of that
22 voltage, within the operational limits of the circuit.

1 Example One: stability

2 Assume that resistors 12, 22, 23 and 24, have equal values of 1.0×10^6 ohms
3 (1.0M ohms); the amplifier gain A , is 1.0×10^6 ; the voltage at node 18, set by reference
4 source 16, is +10 volts; the current generated by the photovoltaic diodes is 10
5 microamperes; the voltage at node 17 is -10 volts; the voltage difference between nodes
6 25 and 26 is 20 volts; and the voltage at node 21 is - 5 volts. The voltage at node 20 is
7 then $+5 \times 10^{-6}$ volts, essentially zero for practical purposes. Since the current through
8 resistor 22 into node 20 is equal to the current through resistor 23 out of node 20, no net
9 current flows into (out of) inverting input 82 of amplifier 13, or through capacitor 14, via
10 node 20. Since no current flows through capacitor 14 the voltage across capacitor 14
11 does not change and driving current 50 through resistor 15 does not change.

12 Example Two: variation correction

13 Assume that an instantaneous variation in ambient conditions, *e.g.*, temperature,
14 occurs such that the voltage drop across resistors 22 and 23 (and thereby across resistors
15 12 and 24) is reduced by 1.0 volt. Since the voltage at node 18 is fixed at +10 volts by
16 reference source 16, and the voltage at node 20 is essentially zero, the voltage at node 17
17 will thereby be -9 volts. The current through resistor 22, into node 20, will still be 10
18 microamperes; the current through resistor 23, out of node 20, will be 9 microamperes,
19 and the net current into node 20, through capacitor 14, will thereby be 1 microampere.
20 Since the voltage across a capacitor is proportional the integral of the current through it
21 as:

22
$$V = (1/C) \int i \, dt$$

1 the voltage across capacitor 14, will begin to change at a rate that satisfies the
2 relation:

3
$$i = C \, dV/dt$$

4 where i is the current flowing through the capacitor, C, is the capacitance in Farads, and
5 V is the voltage across the capacitor. (E.g., let the capacitance, C, be 1×10^{-6} farad and
6 the current be 1 microampere, as above. The voltage across the capacitor 14 will then
7 instantaneously begin to increase at the rate of 1 volt/second.) As the voltage across
8 capacitor 14 increases, the voltage at node 21 becomes increasingly more negative and
9 the driving current 50 increases until a new stable condition exists, such that driving
10 current 50 is of a magnitude to sustain the conditions assumed above in Example One.

11 Fig. 2 depicts an alternate exemplary embodiment wherein bias generation circuit
12 100 comprises multiple optically coupled power sources 111A, 111B and 111C,
13 connected in series. Such configuration provides the potential to develop greater levels
14 of voltage across output node 125 and input node 126 than would be generated by a
15 single similar optically coupled power source (not shown).

16 Referring to Figs. 2, 3 and 4, optically coupled power source 111A is comprised
17 of light emitting diode 135A, and photovoltaic diodes 136A and 137A. Light emitting
18 diode 135A is disposed in such a way that the light from light emitting diode 135A
19 impinges equally on controlled photovoltaic diode set 136A and controlling photovoltaic
20 diode set 137A. Optically coupled power source 111B is comprised of light emitting
21 diode 135B, and photovoltaic diodes 136B and 137B. Optically coupled power source
22 111C is comprised of light emitting diode 135C, and photovoltaic diodes 136C and 137C.

1 Optically coupled power sources 111B and 111C are configured similarly to optically
2 coupled power source 111A, such that light emitting diode 135B is disposed in such a
3 way that the light from light emitting diode 135B impinges equally on controlled
4 photovoltaic diode set 136B and controlling photovoltaic diode set 137B, and light
5 emitting diode 135C is disposed in such a way that the light from light emitting diode
6 135C impinges equally on controlled photovoltaic diode set 136C and controlling
7 photovoltaic diode set 137C.

8 Light emitting diodes 135A, 135B and 135C are connected in series. The anode
9 end of light emitting diode 135C is connected to ground 129, and the cathode end of light
10 emitting diode 135C is connected to the anode end of the next light emitting diode 135B
11 in series. The cathode end of light emitting diode 135B is connected to the anode end of
12 the next light emitting diode 135A in series. The cathode end of light emitting diode
13 135B is connected to resistor 115, which is then connected to output 180 of operational
14 amplifier 113.

15 Controlled photovoltaic diode sets 136A, 136B and 136C generate an electrically
16 isolated controlled current 160, which is essentially equivalent to an electrically isolated
17 controlling current 170 generated by respective, controlling photovoltaic diode sets 137A,
18 137B and 137C.

19 Controlled photovoltaic diode sets 136A, 136B and 136C are connected in series
20 into controlled circuit 130. Output node 125 connects to the anode end of controlled
21 photovoltaic diode set 136C. The cathode end of photovoltaic diode set 136C connects to
22 the anode end of the next photovoltaic diode set 136B in series. The cathode end of

1 photovoltaic diode set 136B connects to the anode end of the next photovoltaic diode set
2 136A in series. Input node 126 connects to the cathode end of controlled photovoltaic
3 diode set 136A.

4 Also connected between input node 126 and output node 125, parallel with
5 controlled photovoltaic diode sets 136A, 136B and 136C are resistors 124 and 112. In
6 the exemplary embodiment, resistors 124 and 112 possess equivalent resistance.

7 Also connected between input node 126 and output node 125, parallel with
8 controlled photovoltaic diode sets 136A, 136B and 136C, and resistors 124 and 112, is
9 capacitor 127. One operational side of capacitor 127 is connected to input node 126 and
10 the other operational side of capacitor 127 is connected to output node 125. In the
11 exemplary embodiment, resistor 128 is also connected to node output 125 intermediate
12 the device intended to use the generated bias voltage.

13 Controlling photovoltaic diode sets 137A, 137B and 137C are connected into
14 controlling circuit 132. Positive output node 118 connects to the anode end of
15 controlling photovoltaic diode set 137C. The cathode end of photovoltaic diode set 137C
16 connects to the anode end of the next photovoltaic diode set 137B in series. The cathode
17 end of photovoltaic diode set 137B connects to the anode end of the next photovoltaic
18 diode set 137A in series. The cathode end of controlling photovoltaic diode set 137A
19 connects to node 117.

20 Positive output node 118 is also connected to a reference voltage source 116. In
21 the exemplary embodiment, reference voltage source 16 is set to +10 volts. Node 117
22 also connects to resistor 123, which in turn connects to node 120. Resistor 122 connects

1 to node 120 on one end and to node 118 on the other. Resistors 123 and resistor 122
2 possess equivalent resistance.

3 Non-inverting input 184 of operational amplifier 13 is connected to ground 19.
4 Inverting input 182 of operational amplifier 113 is connected to node 120 and to the one
5 operational side of capacitor 114. Output 180 of operational amplifier 113 is connected
6 to node 121, which also connects to resistor 115 and the other operational side of
7 capacitor 114.

8 Introducing drive current 150, as sub-currents 150A, 150B and 150C, through
9 light emitting diodes 135A, 135B and 135C, respectively, activates circuit 100. The light
10 emitted by light emitting diodes 135A, 135B and 135C, induces currents 160A, 160B and
11 160C, in photovoltaic diodes 136A, 136B and 136C, respectively, which in series form
12 driven output current 160. At the same time the light emitted by light emitting diodes
13 135A, 135B and 135C, induces currents 170A, 170B and 170C, in photovoltaic diodes
14 137A, 137B and 137C, respectively, which in series form driven feedback current 170.

15 Under stable operating conditions, driven output current 160, generated by photo-
16 voltaic diode sets 136A, 136B and 136C, is essentially equivalent to driven feedback
17 current 170, generated by photovoltaic diode sets 137A, 137B and 137C. Additionally,
18 the voltage across resistors 112 and 124 is equal to the voltage across resistors 122 and
19 123; the voltage at node 117 is equal in magnitude and opposite in sign to the voltage at
20 node 118; and the voltage at node 120, (since the resistors 122 and 123, are of equal
21 value) is essentially zero. The electrically isolated voltage source at nodes 125 and 126 is
22 used as the desired generated bias.

1 Bias generation circuit 100 is configured to seek a stable condition. Since
2 controlled circuit 130 and controlling circuit 132 are subject to the same conditions of
3 loading – e.g., illumination, temperature, etc. – the voltage difference between nodes 125
4 and 126 will be the same as the voltage difference between nodes 118 and 117.

5 The foregoing disclosure and description of the invention is illustrative and
6 explanatory thereof. Various changes in the details of the illustrated construction may be
7 made within the scope of the appended claims without departing from the spirit of the
8 invention. The present invention should only be limited by the following claims and their
9 legal equivalents.